# target

AIMING TO SUCCESS



# Personal 80 g/m<sup>2</sup> Presentations

Aimed to fulfil your print Improves the quality of needs both in the office and at home.



### Personal 90 g/m<sup>2</sup> Letters

your documents and their impact on the reader.



### Personal 100 g/m<sup>2</sup> Cv's

Its superb whiteness will allow you to obtain the best printing contrast in your colour documents.



Personal 110 g/m<sup>2</sup> Colour-intensive documents Guarantees exceptional results in all printing and copying equipment.



Personal 160 g/m<sup>2</sup> Invitations Ready for your personal needs. Ready to Print.



Professional 70 g/m<sup>2</sup> Receipts, Drafts Specially developed to deliver the best machine performance. Designed for the best printing quality in all black & white documents. Redy for your professional needs

Ready to Print.



Professional 75 g/m<sup>2</sup> Corporate 80 g/m<sup>2</sup> Copies, Manuals,

Invoices Ready for all intensive print and copy jobs in any high-volume machine. Enhanced thickness and stiffness for jam-free runnability.



# Guarateed to deliver excellent results in all your documents. Specially developed to

allow double-side use. without show-through. Suitable for all office equipment such as copy and laser machines.

| Whiteness CIE             | ISO 11475     | 171  | 171  | 171  | 171  | 171            | 161  | 161  | 161  |
|---------------------------|---------------|------|------|------|------|----------------|------|------|------|
| Opacity %                 | ISO 2471      | 94   | 96   | 96   | 97   | 98<br>(minium) | 91   | 92   | 93   |
| Moisture %                | ISO 287       | 4,0  | 4,0  | 4,5  | 4,5  | 5,4            | 4,0  | 4,0  | 4,0  |
| Bendtsen Roughness ml/min | ISO 8791/2    | 160  | 140  | 140  | 120  | 150            | 230  | 220  | 180  |
| Thickness µm              | ISO 534       | 108  | 115  | 120  | 131  | 190            | 104  | 106  | 107  |
| Bulk µm / g/m²            | -             | 1,35 | 1,28 | 1,20 | 1,19 | 1,19           | 1,49 | 1,41 | 1,34 |
| Certified                 | PEFC (1)      |      |      |      |      |                |      | Х    | Х    |
| Awarded by                | Eco-label (2) | Х    | Х    | Х    | Х    |                | Х    | Х    | Х    |
| Certified                 | FSC™ (3)      | Х    | Х    | Х    | Х    | Х              |      |      | Х    |

Technical References - Targets only, without tolerances mentioned Basis weight q/m2 - ISO 536

May 2017



www.pefc.org





The mark of responsible forestry

## Additional Information about The Navigator Company Mills and Products:

The Navigator Company mills are chain-of-custody certified by APCER in accordance with PEFC ST 2001 (APCER/2007/CDR.0008).

The Navigator Company mills are chain-of-custody certified by NepCon in accordance with FSC-STD-40-004 (NC-COC-014433) and FSC-STD-40-005 (NC-CW-014433).

In accordance with the requirements of ISO 9706 standard

Elemental Chlorine Free (ECF)

Management Systems certified:

Quality Standard ISO 9001, Environmental Standard ISO 14001, Occupational Health and Safety Standard OHSAS 18001

\* The Ecolabel applies to weights below 120 g/m2.

Please Collect Used Paper for Recycling

